

# UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No. 1293.1133/MJB

First Named Inventor or Application Identifier:

Jae-seong SHIM et al.

Express Mail Label No.

## APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO: Assistant Commissioner for Patents  
Box Patent Application  
Washington, DC 20231

1. ☒ Fee Transmittal Form
2. ☒ Specification, Claims & Abstract ..... [ Total Pages: 16 ]
3. ☒ Drawing(s) (35 USC 113) ..... [ Total Sheets: 3 ]
4. ☐ Oath or Declaration (unsigned).....[ Total Pages:     ]
  - a. ☐ Newly executed (original or copy)
  - b. ☐ Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional with Box 17 completed)
    - i. ☐ **DELETION OF INVENTOR(S)**  
Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation by Reference (usable if Box 4b is checked)  
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.
6. ☐ Microfiche Computer Program (Appendix)
7. ☐ Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
  - a. ☐ Computer Readable Copy
  - b. ☐ Paper Copy (identical to computer copy)
  - c. ☐ Statement verifying identity of above copies

## ACCOMPANYING APPLICATION PARTS

8. ☐ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement (when there is an assignee)    ☐ Power of Attorney
10. ☐ English Translation Document (if applicable)
11. ☐ Information Disclosure Statement (IDS)/PTO-1449    ☐ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503) (Should be specifically itemized)
14. ☐ Small Entity Statement(s)    ☐ Statement filed in prior application, status still proper and desired.
15. ☒ Certified Copy of Priority Document(s) (if foreign priority is claimed)
16. ☒ Other: New Application Fee Transmittal

## 17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No:        /       

## 18. CORRESPONDENCE ADDRESS

STAAS & HALSEY LLP  
Attn: Michael D. Stein  
700 Eleventh Street, N.W., Suite 500  
Washington, DC 20001Telephone: (202) 434-1500  
Facsimile: (202) 434-1501

## TITLE OF INVENTION

### APPARATUS FOR REPRODUCING DATA FROM AN OPTICAL DISC INDUCING VIBRATION AND METHOD THEREOF

## CROSS-REFERENCE TO RELATED APPLICATIONS

5           This application claims the benefit of Korean Application No. 99-27456, filed July 8, 1999, in the Korean Patent Office, the disclosure of which is incorporated herein by reference.

## BACKGROUND OF THE INVENTION

### Field of the Invention

10           The present invention relates to an apparatus for reproducing data from an optical disc, and more particularly, to an apparatus for reproducing data from an optical disc in which a disc inducing vibration is detected and its speed is converted into an appropriate reproducing speed.

### Description of the Related Art

15           Generally, an apparatus for reproducing data from an optical disc which is revolved by a motor can cause serious vibration according to the state of a medium, or cannot read recorded data due to the instability of a servo state.

20           The existing apparatuses for reproducing data from an optical disc typically operate by using a vibration sensor or actuator back electromotive force to detect the disc inducing vibration.

          For example, an apparatus for reproducing data from an optical disc having a vibration sensor increases the speed of a spindle motor so that the revolution speed of the disc is lowered as a function of the amount of a detected signal.

25           Furthermore, an optical disc reproducing apparatus may operate by using back electromotive force to increase the speed of a spindle motor so that the revolution speed of the disc is lowered by back electromotive force induced in an actuator. Such

a disc operates by: 1) increasing the number of revolutions of the spindle motor to a target number of revolutions per minute (RPM); 2) switching focus and tracking to "OFF" states; 3) amplifying back electromotive force induced in a tracking coil and then converting from analog to digital; 4) switching focus and tracking to "ON" states.

5 However, the optical disc reproducing apparatus using the above vibration sensor is disadvantageous because sensing ability varies with the point of attachment of a vibration sensor, and also with respect to the assembled state of the apparatus. Furthermore, the optical disc reproducing apparatus using actuator back electromotive force requires a comparator for checking actuator back electromotive force. This is  
10 disadvantageous because considerable time is spent checking a vibration-inducing disc after focus and tracking are in the "OFF" state. A further disadvantage of this method is that a certain speed factor is constant when a vibration-inducing disc is checked.

## SUMMARY OF THE INVENTION

15 Accordingly, it is an object of the present invention to provide an apparatus and method for detecting a disc inducing vibration and changing the revolution speed as a function of frequency of vibration of the detected disc.

It is a further object of the invention to provide an apparatus and method for reducing the time spent checking a disc after focus and tracking are off.

20 Additional objects and advantages of the invention will be set forth in part in the description which follows, and, in part, will be obvious from the description, or may be learned by practice of the invention.

To accomplish the above objects of the present invention, a first embodiment of the present invention is directed to a method of reproducing data from a disc in a disc-reproducing system, the method having the steps of : (a) positioning a pick-up at a  
25 predetermined location on the disc and counting the number of track traverse pulses generated when tracking is switched to "OFF" at the lowest speed factor; (b) positioning

a pick-up at a predetermined location on the disc and counting the number of track traverse pulses generated when tracking is switched to "OFF" at the highest speed factor; (c) obtaining the frequency of vibration by subtracting the count value of track traverse pulses at the lowest speed factor (counted in step'a') from the count value of track traverse pulses at the highest speed factor (counted in step'b'); and (d) comparing the frequency of vibration obtained in step 'c' with a predetermined base value, and varying the speed factor of reproducing data from the disc based upon this comparison.

A second embodiment of the present invention is directed to a method for reproducing data from a disc in a disc-reproducing system, the method comprising the steps of: (a) positioning a pick-up at a predetermined location on the disc and counting the number of track traverse pulses generated when a tracking loop is switched to "OFF" at an arbitrary speed factor; and (b) comparing the number of the track traverse pulses counted in step 'a' with a pre-determined base value, and varying the speed factor of reproducing data from the disc based upon this comparison.

A third embodiment of the present invention, is directed to an apparatus for reproducing data from a disc inducing vibration, the apparatus having a pick-up unit for detecting a tracking traverse signal by revolving the disc in a tracking "OFF" state; a signal amplifying unit for differentially-amplifying the tracking traverse signal detected by the pick-up unit; a signal comparator for generating a tracking traverse pulse signal after comparing the tracking traverse signal amplified in the signal amplifying unit with a base signal; and a control unit for counting the number of track traverse pulses generated in the signal comparator at the lowest speed factor of the disc and also at the highest speed factor of the disc, obtaining the difference between the two counted numbers, and then determining the frequency of vibration of the disc based upon the difference, and varying the speed factor of the disc as a function of the frequency of vibration.

## BRIEF DESCRIPTION OF THE DRAWINGS

These and other objects and advantages of the invention will become apparent and more readily appreciated from the following description of the preferred embodiments, taken in conjunction with the accompanying drawings of which:

5           FIG. 1 is a conceptual diagram showing the generation of a track traverse signal by vibration;

          FIG. 2 is a block diagram showing an apparatus for reproducing a disc inducing vibration according to the present invention;

10           FIG. 3 is a voltage waveform which measures an actual track traverse signal over a full range of speed factors; and

          FIG. 4 is a flowchart illustrating an example of a method of reproducing a disc inducing vibration according to the present invention.

## DESCRIPTION OF THE PREFERRED EMBODIMENTS

Reference will now be made in detail to the present preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings, wherein like-referenced numerals refer to like-elements throughout.

5 We begin by reviewing the various eccentricities of a disc. A mass eccentric disc causes vibration during reproduction because it has a different center of gravity. An axial eccentric disc causes vibration during reproduction because it has a warped shape and also displays the characteristics of mass eccentricity because of its twisted axis. A net eccentric disc does not cause vibration and only has an eccentric  
10 component because the data on the disc is twisted.

In a mass eccentric disc, weight imbalance causes a centrifugal force, and when the disc operates, the shaft gap of the driving motor causes vibration of the motor axis. Furthermore, chucking of the turntable causes vibration of the axis.

The vibration of a disc axis increases as a function of the speed and the  
15 eccentric degree of a motor. Assuming that the pick-up is fixed, the vibration of the motor axis causes vibration in reproducing because it has a warped shape and the characteristics of mass eccentricity because of its twisted axis. A net eccentric disc does not cause vibration and only has an eccentric component because recording of the disc is twisted.

20 In a mass eccentric disc, unbalance in the weight causes a centrifugal force, and the shaft gap of the driving motor, when the disc operates, causes vibration of the motor axis. In addition, chucking of the turntable causes vibration of the axis.

The vibration of a disc axis increases with respect to the speed and eccentric  
25 degree of a motor. When it is assumed that the pick-up is fixed, the axis vibration causes a disc to move from side to side with each revolution as viewed from the object lens of the pick-up.

As a result, as shown in FIG. 1, with the pick-up unit 220 (not shown) fixed, a disc 210 is moved by axis variation (axis vibration), and disc migration causes a track

1 traverse signal in the form of an analog frequency. That is, 110 in FIG. 1 can be the  
2 migration length caused by the vibration.

Using this track traverse signal, the present invention determines the frequency  
of vibration.

5 A net eccentric disc causes a lot of track traverse signals both at a lower speed  
factor and at a higher speed factor. This differs from an axial eccentric disc and a mass  
eccentric disc which do not cause vibration at a lower speed factor and therefore, cause  
few track traverse signals. However, at a higher speed factor, they cause vibration and  
therefore cause strong track traverse signals.

10 Accordingly, by comparing a track traverse signal at a lower speed factor with  
that at a higher speed factor, it is determined whether or not an axial eccentric disc or a  
mass eccentric disc causes the vibration.

FIG. 2 is a block diagram showing an apparatus 200 for reproducing disc  
inducing vibration according to the present invention. The apparatus has a pick-up unit  
15 220, an error detecting unit 230, an error amplifying unit 240, a signal comparator 250,  
a microcomputer 260, and a spindle motor 270.

First, the pick-up unit 220 is provided with photodiodes (E,F) (not shown). The  
photodiodes (E,F) detect a tracking traverse signal from the revolving disc 210 when  
focus is "ON" and the tracking loop is "OFF". At this time, the pick-up unit 220 is set to  
20 a predetermined voltage at its innermost circumference. Tracking is "OFF" for a full  
range of speed factors in order to minimize an error from shaking and a measuring  
error.

The error detecting unit 230 calculates the tracking traverse signal, which was  
detected by the pick-up unit 220, in an E-F form. Next, the error amplifying unit 240  
25 differentially-amplifies the E-F form tracking traverse signal calculated in the error  
detecting unit 230, and sends the amplified signal to the signal comparator 250. The  
comparator 250 compares the amplified signal to a base signal, and then generates a  
pulse signal. The microcomputer 260 then determines the frequency of vibration by

counting pulse signals generated in the signal comparator 250 at the lowest speed factor of the disc and at the highest speed factor of the disc. Then the revolution of the spindle motor is increased or decreased as a function of the frequency of vibration.

Specifically, in order to determine whether or not a disc is axial eccentric or mass eccentric, the microcomputer 260 subtracts the counted value of the track traverse signal at a lower speed factor from the counted value of the track traverse signal at a higher speed factor. The frequency of vibration is determined by dividing the difference between the counted values by the number of revolutions of the spindle. Then, the revolution speed is varied by comparing the frequency of vibration with a base value.

For example, when the frequency of vibration is greater than or equal to 80Hz, the speed factor is set to 16 times the lower speed factor. This lower speed factor is used because the vibration is great. When the frequency of vibration is greater than or equal to 40Hz (but less than 80Hz), the speed is set to 20 times the lower speed factor. When the frequency of vibration is less than 40Hz, the speed is set to 24 times the lower speed factor. This higher speed factor is used because the vibration is small. After setting the speed factor, the microcomputer 260 switches tracking "ON" and resumes normal reproduction of data from the disc.

FIG. 3 is a voltage waveform which measures an actual track traverse signal over a full range of speed factors in order to reduce disc shaking and measuring errors.

Referring to FIG. 3, the microcomputer 260 (not shown) switches tracking "OFF" by applying a track-off voltage to the driving motor of the pick-up unit 220 (not shown). In this state, the microcomputer 260 checks the innermost circumference of the disc 210 (not shown). The microcomputer 260 counts the number of pulses of a track traverse signal after a predetermined time, for example, 2 revolutions of the disc (about 100ms delay). After the microcomputer 260 counts the pulses, it switches tracking "ON" by applying a track-on voltage to the driving motor.

FIG. 4 is a flowchart illustrating an example of a method of reproducing data from a disc inducing vibration according to the present invention.



First, the disc is started up by switching focus "ON" and switching tracking "OFF" (step 410).

In step 420, after switching tracking to "OFF" at one times the lower speed factor, in order to limit the movement range of the pickup, a microcomputer 260 detects whether the pickup has reached the innermost circumference of the disc using a limit switch (not shown). After a predetermined time passes, the number of track traverse pulses is counted.

In step 430, the constant angular velocity (CAV), which increases from inner circumferences to outer circumferences, is started.

In step 440, the disc is revolved until the speed reaches 3700RPM.

In step 450, the speed is 3700RPM, and tracking is switched to "OFF" at the highest speed factor, for example, at 24 times speed. Then, at a predetermined time after checking the innermost circumference of the disc, the number of pulses of the track traverse signal is measured.

In step 460, the frequency of vibration is measured by subtracting the number of traverse pulses at the lowest speed factor (1 times speed) from the number of traverse pulses at the highest speed factor (24 times speed).

In steps 470 and 480, the measured frequency of vibration is compared with predetermined basis frequencies (for example, 80Hz and 40Hz).

In steps 472, 482 and 484, the speed factor is set according to the measured vibration frequency. When the measured frequency of vibration is 80Hz or more (large vibration), the speed factor is set to a lower speed factor (16 times speed) in order to reduce vibration. When the measured frequency of vibration is less than 80Hz and greater than or equal to 40Hz, the speed factor is set to 20 times speed. When the measured frequency of vibration is less than 40Hz, the disc is determined to have a small vibration and a higher speed factor (24 times speed) is set. At this time, the base of the speed factor can be set to 45dB noise or less.

As described above, according to the present invention, an appropriate speed factor can be set with respect to the frequency of vibration of a disc.

Furthermore, because the frequency of vibration is checked with focus "ON", the invention realizes the advantage of faster tracking.

5           Although a few preferred embodiments of the present invention have been shown and described, it would be appreciated by those skilled in the art that changes may be made in these embodiments without departing from the principles and spirit of the invention, the scope of which is described in the claims and their equivalents.

What is claimed is:

- 1           1.     A method of reproducing data from a disc in a disc-reproducing system,  
2     the method comprising:  
3           (a) positioning a pick-up at a predetermined position on the disc and counting a  
4     number of track traverse pulses which are generated when a tracking is switched to  
5     "OFF" at a lowest speed factor;  
6           (b) positioning the pick-up at a predetermined position on the disc and counting a  
7     number of track traverse pulses which are generated when a tracking is switched to  
8     "OFF" at a highest speed factor;  
9           (c) obtaining a frequency of vibration of the disc by subtracting the number of  
10    track traverse pulses at the lowest speed factor from the number of track traverse  
11    pulses at the highest speed factor; and  
12           (d) varying a speed factor of reproducing data from the disc, by comparing the  
13    frequency of vibration with a predetermined base value.  
  
1           2.     The method of reproducing data from a disc in a disc-reproducing system  
2     of claim 1, wherein one of the steps (a) and (b) further comprises checking an  
3     innermost circumference of the disc after tracking is switched to "OFF", and at a  
4     predetermined time after checking the innermost circumference of the disc, counting  
5     the number of track traverse pulses when the counting is switched to "OFF" at a  
6     corresponding speed factor.  
  
1           3.     A method of reproducing data from a disc in a disc-reproducing system,  
2     the method comprising:  
3           (a) positioning a pick-up at a predetermined position on the disc and counting a  
4     number of track traverse pulses which are generated when a tracking loop is switched  
5     to "OFF" at an arbitrary speed factor; and

(b) varying a speed factor of reproducing data from the disc, by comparing the number of track traverse pulses with a predetermined base value.

4. An apparatus for reproducing data from a disc inducing vibration, the apparatus comprising:

a pick-up unit detecting a tracking traverse signal by revolving the disc in a tracking "OFF" state;

a signal amplifying unit differentially-amplifying the tracking traverse signal detected by the pick-up unit;

a signal comparator generating a tracking traverse pulse signal comprised of at least one tracking traverse pulse after comparing the tracking traverse signal amplified in the signal amplifying unit with a base signal; and

a control unit counting the number of tracking traverse pulses generated by the signal comparator at a lowest speed factor of the disc and also at a highest speed factor of the disc, obtaining the difference between the two counted numbers, and then determining a frequency of vibration of the disc based upon the difference, and varying a speed factor of the disc as a function of the frequency of vibration.

5. The apparatus for reproducing data from a disc inducing vibration of claim 4, wherein the control unit counts the number of track traverse pulses at a predetermined time after checking an innermost circumference of the disc when tracking is switched to "OFF".

6. A method of reproducing data from a revolving disc in a disc-reproducing system, comprising:

counting a number of track traverse pulses at a first revolving speed;

counting a number of track traverse pulses at a second revolving speed;

5 determining a frequency of vibration of the disc by comparing the number of  
6 track traverse pulses counted at the first revolving speed with the number of track  
7 traverse pulses counted at the second revolving speed.

1 7. The method of reproducing data from a disc in a disc-reproducing system  
2 of claim 6, further comprising:  
3 comparing the determined frequency of vibration of the disc with a  
4 predetermined base value; and  
5 revolving the disc at a reproducing speed based upon the comparison of the  
6 determined frequency of vibration with the predetermined base value.

1 8. The method of reproducing data from a disc in a disc-reproducing system  
2 of claim 7, wherein the first revolving speed is slower than the second revolving speed.

1 9. The method of reproducing data from a disc in a disc-reproducing system  
2 of claim 8, wherein the second revolving speed is approximately 24 times the first  
3 revolving speed.

1 10. The method of reproducing data from a disc in a disc-reproducing system  
2 of claim 9, wherein the reproducing speed is decreased with increased frequency of  
3 vibration.

1 11. The method of reproducing data from a disc in a disc-reproducing system  
2 of claim 10, wherein the reproducing speed is approximately 16 times the first revolving  
3 speed when the frequency of vibration is determined to be greater than or equal to  
4 80Hz, the reproducing speed is 20 times the first revolving speed when the frequency of  
5 vibration is determined to be greater than or equal to 40Hz and less than 80Hz, and the

6 reproducing speed is 24 times the first revolving speed when the frequency of vibration  
7 is determined to be less than 40Hz.

1 12. The method of reducing data from a disc in a disc-reproducing system of  
2 claim 11, wherein the disc further comprises an inner circumference and the disc-  
3 reproducing system includes tracking comprising "OFF" and "ON" states, further  
4 comprising:  
5 switching tracking in the disc-reproducing system to the "OFF" state; and  
6 checking the innermost circumference of the disc.

1 13. The method of reproducing data from a disc in a disc-reproducing system  
2 of claim 12, wherein the counting of track traverse pulses at the first revolving speed  
3 and the second revolving speed comprises counting the track traverse pulses at a  
4 predetermined time after checking the innermost circumference of the disc.

1 14. The method of reproducing data from a disc in a disc-reproducing system  
2 of claim 13, wherein the predetermined time after checking the innermost  
3 circumference of the disc is approximately equal to a time for the disc to complete two  
4 revolutions.

1 15. The method of reproducing data from a disc in a disc-reproducing system  
2 of claim 13, wherein the predetermined time after checking the innermost  
3 circumference of the disc is approximately 100ms.

1 16. An apparatus for reproducing data from a disc inducing vibration, the  
2 apparatus comprising:  
3 a pick-up unit detecting a tracking traverse signal;

4 a signal comparator comparing the tracking traverse signal with a base signal  
 5 and then generating a tracking traverse pulse signal comprised of at least one tracking  
 6 traverse pulse; and  
 7 a control unit counting the number of track traverse pulses generated in the  
 8 signal comparator.

1 17. The apparatus for reproducing data from a disc inducing vibration of claim  
 2 16, wherein the control unit counts the number of track traverse pulses generated in the  
 3 signal comparator at a first revolving speed of the disc and also at a second revolving  
 4 speed of the disc, determines a frequency of vibration of the disc based upon the track  
 5 traverse pulse counts, and changes a speed of the disc based upon the frequency of  
 6 vibration of the disc.

1 18. The apparatus for reproducing data from a disc inducing vibration of claim  
 2 17, wherein the pick-up unit further comprises a tracking "OFF" state and a tracking  
 3 "ON" state, and the pick-up unit detects a tracking traverse signal by revolving the disc  
 4 in the tracking "OFF" state.

1 19. The apparatus for reproducing data from a disc inducing vibration of claim  
 2 18, further comprising a signal amplifying unit to differentially amplify the tracking  
 3 traverse signal detected in the pick-up unit prior to sending the signal to the signal  
 4 comparator.

1 20. The apparatus for reproducing data from a disc inducing vibration of claim  
 2 19, wherein the control unit counts the number of track traverse pulses at a  
 3 predetermined time.

1           21.    The apparatus for reproducing data from a disc inducing vibration of claim  
2    20, wherein the predetermined time for counting the number of track traverse pulses is  
3    approximately 100ms after checking an innermost circumference of the disc.



## ABSTRACT OF THE DISCLOSURE

A method and apparatus for reproducing data from an optical disc in which a disc inducing vibration is detected and the speed of the disc is adjusted to an appropriate speed which does not cause vibration. The method includes obtaining the frequency of vibration by subtracting the count value of track traverse pulses at the lowest speed factor from the count value of track traverse pulses at the highest speed factor; and varying the speed factor of reproducing data from the disc based upon a comparison of the obtained frequency of vibration with a predetermined base value.

FIG. 1




FIG. 2




FIG. 3




FIG. 4

